

Model DPT-40B

PULLER-TENSIONER



The DPT-40B is a proven hydrostatic pulling and tensioning system with hydraulic oil cooler and water cooled diesel engine. The DPT-40B is mounted on a dual axle trailer with leaf spring suspension with a reel capacity of 1828 mm (72") diameter, 1422 mm (56") wide and 2722 kg (6,000 lbs.).

This unit provides infinitely variable line speed and line pull control with a free wheeling disconnect for high speed rope payout.

The operator is positioned centrally behind a safety screen for maximum safety and visibility. This unit is equipped with a spring applied, hydraulic pressure release holding brake for protection in the event of engine or hydraulic failure.

Performance Features

Continuous torque rating Intermittent torque rating Continuous linepull rating

790 daNm (70,000 in.lbs) 904 daNm (80,000 in.lbs)

1973 kg with 1829 m of 16mm rope on drum (4,350 lbs. with 6,000 ft. of 5/8" rope on drum)

Speed 6.4 km/h (4 mph) with infinite speed control

REEL CAPACITY

 Maximum reel diameter
 1828 mm (72")

 Maximum reel width
 1422 mm (56")

 Maximum reel weight
 2722 kg (6,000 lbs.)

 Shaft diameter
 66 mm (2 5/8")

DRIVE SYSTEM

Water cooled brand name diesel engine 37 kW (50 hp) Hydraulic drive - closed loop hydrostatic Drive train brake spring applied / hydraulic pressure released

TRAILER SPECIFICATIONS

Axles tandem with leaf spring suspension **Trailer Brakes** 12 x 2 electric on each wheel (4) 8.75 x 16.5 LT - 10 ply rating Tires **GAWR** 4718 kg (10,400 lbs) **GVWR** 5262 kg (11,600 lbs) Tow hitch 76 mm (3") pintle eye with 4 height adj. Front jack manual screw jack with drop leg Trailer lighting 4 light system

GENERAL FEATURES

45.4 L (12 gallon) fuel reservoir with level gauge 68.1 L (18 gallon) hydraulic reservoir with level & temp gauge Hydraulic cooler for positive heat dissipation Drive freewheeling disconnect for payout of pulling rope Quick change reel shaft removal Steel lockable battery box

PHYSICAL DIMENSIONS

Weight (Approximate) Length (Approximate) Width (Approximate) Height (Approximate) 1814 kg (4,000 lbs) 4400 mm (174") 2300 mm (91") 1800 mm (70")

OPTIONS

High speed polemaster™ pilot rope drive
High speed polemaster™ levelwind
Hydraulic overhead levelwind
Bronze overspin payout brake
Operator's seat
Combination overhead / underground levelwind
Underground pulling drum
4440 heavy duty pulling drum
BR6030 breakaway reel
Mechanical drop-leg rear jacks
Hydraulic front jack
Gasoline engine

OUR PEOPLE CARE . . . OUR EQUIPMENT IS THE PROOF

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE

Timberland Equipment Limited www.timberland.on.ca

PO Box 490, 459 Industrial Avenue Woodstock, Ontario, Canada N4S 7Z2

Phone: (519) 537-6262 Fax: (519) 539-5853 Web: www.timberland.on.ca Email: sales@tewinch.com