

## ACCESSORIES

| Model                                      | S-16   |    | S-20  |    | S-32   |    | S-40  |    | S-55   |    | S-85   |    |
|--|--|----|---|----|--|----|---|----|--|----|--|----|
| Maximum cutting capacities (shown in O.D.) | Output 4.40 Tons<br>Weight 6.2 lbs<br>Length 15" |    | Output 4.40 Tons<br>Weight 6.4 lbs<br>Length 15 1/8"<br>Insulated handle tested to 20,000 volts |    | Output 19.84 Tons<br>Weight 21 lbs<br>Length 26 3/4" |    | Output 6.28 Tons<br>Weight 11.5 lbs<br>Length 22" |    | Output 13.12 Tons<br>Weight 22 lbs<br>Length 24 3/4" |    | Output 3 Tons<br>Weight 15.5 lbs<br>Length 26" |    |
|  | in.  | mm | in.   | mm | in.  | mm | in.   | mm | in.  | mm | in.  | mm |
| 6 x 7 Hempcore or IWRC                     | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 3/4   | 20 | 1  | 26 | Do not cut                                     |    |
| 6 x 12 Hempcore or IWRC                    | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 3/4   | 20 | 1  | 26 | Do not cut                                     |    |
| 6 x 19 Hempcore or IWRC                    | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 3/4   | 20 | 1  | 26 | Do not cut                                     |    |
| Copper wire or bar                         | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 3/4   | 20 | 1.26   | 32 | Do not cut                                     |    |
| Aluminum wire or bar                       | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 3/4   | 20 | 1.26   | 32 | Do not cut                                     |    |
| Soft steel bolts                           | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 3/4   | 20 | 7/8  | 22 | Do not cut                                     |    |
| Reinforcing bar                            | Do not cut                                       |    | Do not cut  |    | 1  | 26 | Do not cut  |    | Do not cut   |    | Do not cut                                     |    |
| Bare copper wire strands                   | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 1.48  | 37 | 2  | 50 | 1.6  | 41 |
| Bare aluminum wire strands                 | 5/8  | 16 | 3/4   | 20 | 1 1/4  | 32 | 1.60  | 40 | 2  | 50 | 1.8  | 46 |
| ACSR                                       | 5/8  | 16 | 25/32   | 21 | 1 1/4  | 32 | 1.62  | 41 | 2  | 50 | Do not cut                                     |    |
| Galv. steel wire 1 x 7                     | 9/16   | 14 | 9/16  | 14 | 1  | 26 | 5/8   | 16 | 3/4  | 20 | Do not cut                                     |    |
| Galv. steel wire 1 x 19                    | 9/16   | 14 | 9/16  | 14 | 1  | 26 | 5/8   | 16 | 3/4  | 20 | Do not cut                                     |    |
| Telephone cable CCP                        | Not recommended                                  |    | Not recommended   |    | Not recommended                                      |    | Not recommended                                   |    | Not recommended                                      |    | 3.35   | 85 |
| Lead sheathed cable (telephone cable)      | Not recommended                                  |    | Not recommended   |    | Not recommended                                      |    | Not recommended                                   |    | Not recommended                                      |    | 3.35   | 85 |
| Underground cable (power)                  | 5/8  | 16 | 23/32   | 18 | Not recommended                                      |    | 1.62  | 41 | 1.62   | 41 | 3.35   | 85 |



**OUR PEOPLE CARE ...  
OUR EQUIPMENT IS THE PROOF**

## TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE