

## ACCESSORIES

Accuracy: +/- 0.5% of full scale capacity for precise data.

Broadest range of capacities and resolutions are certain to fit your needs.

Wide temperature range for use in nearly any environment. (-45 to 60°C / -50 to 140°F)

Large safety factor for overload protection and long life.

No batteries required.

Dial size choice for the best in portability or visibility.

Anti-parallax dial and pointer produce accurate readings from any perspective.

Maximum hand retains peak load point and is easily reset.

Zero control cancels preset loads (backside).

High strength case resists heavy blows.

Generous shackle openings mate with most hooks and hardware

High specification materials on all load components. Heat treated to tight tolerances.

Durable powder coat paint provides outstanding protection.

Offset load beam eases tension measurement



Digital Available

250mm (10") Dial size			
Kilogram Capacities		Pound Capacities	
Capacity	Division Size	Capacity	Division Size
200	1	500	2
500	2	1,000	5
1,000	5	2,000	10
2,000	10	4,000	20
4,000	20	5,000	20
5,000	50	6,000	25
10,000	50	8,000	50
15,000	100	10,000	50
20,000	100	15,000	100
		20,000	100
		30,000	200
		40,000	200
		50,000	200

125mm (5") Dial size			
Kilogram Capacities		Pound Capacities	
Capacity	Division Size	Capacity	Division Size
200	2	500	5
500	5	1,000	10
1,000	10	2,000	20
2,000	20	4,000	25
4,000	25	5,000	50
5,000	50	6,000	50
10,000	100	8,000	50
		10,000	100
		15,000	100
		20,000	200

**OUR PEOPLE CARE ...  
OUR EQUIPMENT IS THE PROOF**

## TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE