

POWER RODDER**Model S660**PERFORMANCE FEATURES

OK Champion Rodders set the standard for continuous rodding equipment. The S66 and S660 Rodders are easy to use and flexible enough to tackle all duct and sewer rodding jobs. All OK Champion Rodders feature fast simple operation of the rod - forward/reverse action, clockwise/counterclockwise rotation, lateral movement and braking action - all performed with a convenient one-hand control. Visual hydraulic gauges indicate pressure of lateral and rotation circuits at all times. Controls are located for the convenience of the operator.

These continuous power rodders are designed for heavy duty rodding of telephone and power conduit, sanitary and storm sewer lines. They are capable of pushing continuous rod up to 300 meters (1000') in conduit without spinning. In extreme circumstances where plugging or mis-alignment of the duct has occurred, the rod can be rotated to a maximum distance of 450 meters (1500').

The drive head is totally hydraulically driven - no chains, belts, sprockets, pulleys or countershafts! This superior S66/S660 drive head reduces "down time" since there are fewer moving parts susceptible to normal wear and replacement. Powerful dual stage hydraulic drive allows complete independence of lateral and rotation speeds. Two hydraulic motors mounted on the drive head provide power directly to the three pairs of gear driven, heat treated steel drive rolls. The S66 Rodders feature pre-set manual drive roll torquing, while the S660 utilizes proportional hydraulic torquing for longer rod life and greater pulling power.

See other side for equipment features and specifications.

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE

POWER RODDER

Model S660

SPECIFICATIONS

Pulling Force	3175 kg (7000 lbs.)
Rod Speed	61 m/min (200 fpm)
Rod Diameter	9.52 mm (.375") - 11.71 mm (.461")

STANDARD FEATURES

Rod distance meter
Lateral pressure control
Rotation pressure control
Rod Oiler

EXCLUSIVE FEATURES

Unitized control handle
Direct hydraulic drive
700 m (2300 ft.) rod capacity
Rolled drive roll gears
Enclosed rod drive

OPTIONS

Flexible or rigid rod guide set
Cable pulling guide sets
Manhole dewatering pump
Manhole ventilator
Rod wash down system

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE