

DRUM PULLER


The DP10-4H is a compact and portable hydraulically powered 4 drum puller. Designed as a light distribution puller, it can also serve as a pilot line winder. The pulling unit can be removed from the trailer and pole mounted with power supplied by the integral power-pack or from a line truck. Power is transmitted to the drums through a common drive train. A diamond leadscrew levelwind accommodating one reel at a time, provides an even wrap during the pull. Individual overspin brakes can be controlled manually or with a hot stick.

PERFORMANCE

(based on 57 liters/min @ 13.8 Mpa / 5 gpm @ 2000 psi)

Rated linepull

Empty drum	734 daN (1650 lbs)
Full drum	389 daN (875 lbs)

Max linepull (@ 20 Mpa (3,000 psi) intermittent)

Empty drum	888 daN (2000 lbs)
Full drum	444 daN (1000 lbs)

Linespeed

Empty drum	0-82 m/min (0-270 fpm)
Full drum	0-164 m/min (0-540 fpm)

Average linespeed

120 m/min (396 fpm)

Reel Capacity

8 mm (5/16") rope	2591 m (8,500 ft)
10 mm (3/8") rope	1829 m (6,000 ft)
11 mm (7/16") rope	1371 m (4,500 ft)
12 mm (1/2") rope	1066 m (3,500 ft)

STANDARD EQUIPMENT

Single axle trailer with 2,358 kg (5200 lbs) axle
 13 kW (18 hp) air-cooled engine
 22 liter (6 gallon) fuel tank
 44 liter (12 gallon) hydraulic tank
 Diamond leadscrew levelwind
 Free wheeling drums with disc overspin brakes
 Fine control manual calipers on overspin brakes
 Individual drum clutches
 Anti-rotation device on drive system

UNIT DIMENSIONS (Approx.)

Length	3429 mm (135")
Width	2337 mm (92")
Height	1880 mm (74")
Weight (w/o rope)	1451 kg (3200 lbs)

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE