

DRUM PULLER



SPECIFICATIONS

Performance

Continuous linepull 13,345 daN (30,000 lbs) @ 3.0 mph
22,240 daN (50,000 lbs) @ 2.1mph

Drum Capacity

9,574 m of 16 mm (32,000 ft of 5/8") rope
6,705 m of 19 mm (22,000 ft of 3/4") rope
4,878 m of 22 mm (16,000 ft of 7/8") rope

Engine (diesel) 320 kW (430 hp)

OPERATOR'S CONTROLS

Direction control lever with infinite speed adjustment
Adjustable pull/tension control with bypass if preset linepull is reached
Speed range selector low/medium/high
Holding brake apply/release control
Hydraulic system pressure gauge
Engine throttle control
Remote reel stand direction and linepull control
Permanently engraved control panel

STANDARD EQUIPMENT

Proven hydrostatic pulling system with infinitely variable linespeed and linepull control
Spring applied / hydraulically released holding brake
Automatic diamond leadscrew levelwind system for even spooling of rope onto drum
Auxiliary hydraulic system for remote mounted reel winder
150 gallon hydraulic reservoir with level and temperature gauge
Hydraulic fan driven oil cooler with thermostat for positive heat dissipation
Hydraulic controls for remote reel winder

OPTIONS

Trailer mounting - fifth wheel, tandem axle including air brakes, breakaway connections with fenders and mudflaps
High regulation lighting
Hydraulic operated levelwind boom
Heavy duty collapsable cab, complete with shatter resistant plexiglass, protective wire screen with heater

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE