

**FIBRE OPTICS PULLER**

**SPECIFICATIONS**

Maximum continuous torque	350 daN-m (31,000 in.lbs)
Maximum continuous linepull*	590 daN (1300 lbs)
Average linespeed	4.8 km/h (3 mph)
Drum diameter	1016 mm (40")
Drum width	826 mm (32.5")
Drum capacity, synthetic rope	4720 m of 9.5 mm (15,000 ft of 3/8")
Engine (gasoline)	13 kW (18 hp)
Weight	2268 kg (5000 lbs)
Length (Approx.)	4216 mm (166")
Width (Approx.)	2260 mm (89")
Height (Approx.)	1980 mm (78")

\* linepull rated at full drum

**STANDARD EQUIPMENT**

Fully hydraulic drive system  
 Infinitely variable speed and linepull control  
 Automatic overpull protection system  
 Single axle trailer mounted with electric trailer brakes and highway lighting package  
 One front and two rear jacks  
 Free wheeling disconnect  
 Bronze disc overspin brake  
 Operator's seat and protective screen

**OPTIONS**

Hydraulic front jack  
 Diesel engine  
 Chart recorder system

**OUR PEOPLE CARE ...  
 OUR EQUIPMENT IS THE PROOF**

**TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE**