

BULLWHEEL PULLER

SPECIFICATIONS
Model P80-1H/1DD

Maximum linepull	8000 daN (17,990 lbs)
Maximum linespeed	5 km/hr (3.1 mph)
Bullwheel diameter	457 mm (18")
Maximum rope diameter	18 mm (11/16")
Power (Diesel)	82 kW (110 hp)
Weight (Approx.)	2360 kg (5200 lbs)
Length (Approx.)	3100 mm (122")
Width (Approx.)	2210 mm (87")
Height (Approx.)	2140 mm (84")

Model P100-1H/1DD

Maximum linepull	10,000 daN (22,500 lbs)
Maximum linespeed	5 km/hr (3.1 mph)
Bullwheel diameter	508 mm (20")
Maximum rope diameter	22 mm (7/8")
Power (Diesel)	97 kW (130 hp)
Weight (Approx.)	2500 kg (5500 lbs)
Length (Approx.)	3300 mm (130")
Width (Approx.)	2235 mm (88")
Height (Approx.)	2140 mm (84")

STANDARD FEATURES

- Fully hydraulic drive system
- Direct drive bullwheels, no chains or gears
- Infinitely variable speed and linepull control
- Automatic overpull protection system
- Water-cooled diesel power unit
- Spring applied / hydraulic released brakes
- Single axle trailer
- Auxiliary hydraulic circuit for separate reelwinder

OPTIONS

- Highway package
- Integral self-loading reelwinder for reel sizes up to 1400 mm (55") diameter, 600 mm (24") wide, 2000 kg (4400 lbs)
- Console cover

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE