

**BULLWHEEL PULLER**

PERFORMANCE FEATURES

Maximum Linepull	1 x 24000 daN (53,954 lbs)
Maximum Linespeed	5 km/hr (3.1 mph)

PULLER BULLWHEEL SPECIFICATIONS

Bullwheel diameter	914 mm (36")
Maximum rope diameter	38 mm (1.5")
11 machined grooves per bullwheel set	53 mm (2.4")

ENGINE SPECIFICATIONS

Water-cooled diesel engine 12V electric system	279 kW (375 hp)
---	-----------------

MECHANICAL DRIVE SPECIFICATIONS

Bullwheels driven by fully enclosed planetary gearbox drive  
 Infinite variable speed, linepull control  
 Automatic over-pull protection system with linepull gauge  
 Heavy duty hydraulic oil cooler  
 Replaceable hydraulic oil filters complete with visual dirt alarms

SAFETY FEATURES

Spring applied / hydraulic pressure released brakes on bullwheel drives  
 apply automatically in the event of hydraulic circuit pressure loss or  
 engine shutdown  
 Overpull protection to set maximum linepull

PHYSICAL DIMENSIONS

Weight (Approx.)	5,534 kg (12,200 lbs)
Length (Approx.)	6225 mm (245")
Width (Approx.)	2260 mm (89")
Height (Approx.)	2718 mm (107")

OPTIONS

Side mount operator's seat  
 Air-ride axle suspension  
 Highway lighting  
 Air actuated trailer brakes

**OUR PEOPLE CARE ...  
OUR EQUIPMENT IS THE PROOF**

**TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE**