

TENSIONER / REEL CARRIER

SPECIFICATIONS

Maximum continuous tension	1360 daN (3000 lbs)
Maximum linespeed	6.4 km/h (4.0 mph)
Bullwheel diameter	914 mm (36")
Bullwheel grooves	4 @ 32 mm (1.25")
Maximum reel weight	3175 kg (7000 lbs)
Maximum reel diameter	1828 mm (72")
Maximum reel width	1320 mm (52")
Length (Approx.)	4200 mm (198")
Width (Approx.)	1900 mm (90")
Height (Approx.)	2000 mm (94")
Weight (Approx.)	1635 kg (3600 lbs)

STANDARD EQUIPMENT

Smooth control of conductors
 Hydraulic bronze disc brakes with equal retarding to each bullwheel
 Open reeve bullwheels for easy conductor installation and removal
 Replaceable urethane bullwheel lining segments
 Tail fairlead with 3 rubber lined rollers
 Tandem axle with leaf spring suspension
 Quick change reel shaft with straight vertical lift
 406 mm (16") bronze disc reel brake with manual caliper
 Electric actuated trailer brakes
 One front and two rear manual jacks

OPTIONS

Manual reel shaft rewinder
 Hydraulic reel shaft rewind

OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE