

TENSIONER / REEL CARRIER

SPECIFICATIONS

Maximum tension	1360 daN (3000 lbs)
Maximum linespeed	4.0 km/h (2.5 mph)
Bullwheel diameter	914 mm (36")
Bullwheel grooves	4 @ 32mm (1.25")
Engine power	5 kW (6.5 hp)
Maximum reel weight	2730 kg (6000 lbs)
Maximum reel diameter	1828 mm (72")
Maximum reel width	1120 mm (44")
Weight (Approx.)	2722 kg (6000 lbs)
Length (Approx.)	5790 mm (228")
Width (Approx.)	2235 mm (88")
Height (Approx.)	2438 mm (96")

STANDARD EQUIPMENT

Infinitely variable speed control
 Infinitely variable tension control
 Spring applied / hydraulic released brake
 Air-cooled diesel engine
 Replaceable urethane bullwheel lining segments
 Integral reel carrier with 406 mm (16") hydraulic bronze disc brake for tensioning
 Quick change 67 mm (2 5/8") diameter reel shaft
 Tandem axle trailer mounted
 Electric actuated trailer brakes
 One front and two rear manual jacks

OPTIONS

Highway package
 Hydraulic jacks
 Lockable console cover
 13.4 kW (18 hp) diesel engine for pullback includes hydraulic drive on reel carrier (shown above)

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE