

TENSIONER MODULES



FEATURES:

- Easily adapted to truck or trailer mounting
- Fine pressure control for tensioning brake(s)
- Open side construction for ease in threading conductor
- Input fairleads with urethane rollers are standard

	Model 3502	Model 3504
Tensioner Type	Single Bullwheel “V” Groove	Double Bullwheel Multi-Groove
Rated Tension	3000 lbs @ 4 mph / 1360 kg @ 6.4 km/h	3000 lbs @ 4 mph / 1360 kg @ 6.4 km/h
Bullwheel size	36” / 914 mm diameter	36” / 914 mm diameter
Linings	Single Groove / Replaceable Urethane	4 Groove / Replaceable Urethane
Max Conductor Diameter	1.75” / 44 mm	1.25” / 31.75 mm
Tensioning Brake(s)	36” / 914 mm diameter Bronze Disc	2 x 24” / 610 mm diameter Bronze Disc
Module Length	48” / 1219 mm	50” / 1270 mm
Module Width	34” / 864 mm	45” / 1143 mm
Module Height	52” / 1321 mm	58” / 1473 mm
Weight	500 lbs. / 227 kg	900 lbs. / 408 kg

**OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE