

## ACCESSORIES



LSB-B Models are available with optional load limiters. Also featuring through-hardened load chain, these stamped steel ratchet lever hoists are lightweight, durable and are ideal for construction and commercial applications. All LSB-B hoist are metric rated.

**CAPACITIES AND LIFT** - Rated loads of 3/4, 1 1/2, 3 and 6 tons with 5, 10, 15 and 20 foot standard lifts. Other lifts available.

**OPTIONAL LOAD LIMITER** - Load Limiter alerts operator of a possible overload by allowing the handle to rotate without lifting the higher-than capacity load. The load limiter can be field installed.

**RUGGED AND LIGHTWEIGHT** - Impact resistant, stamped steel housing withstands rigorous use. Compact design is portable and easy to rig.

**LOW HANDLE EFFORT** - Double reduction gearing and short, cushioned-grip handle provide easy operation with minimal handle effort.

**360° ROTATING HANDLE** - Provide versatile rigging options when used in confined spaces.

**EASY FREE CHAINING** - State-of-the-art free wheeling mechanism allows quick and easy one-handed take-up and positioning of slack chain.

**POSITIVE LOAD CONTROL** - Enclosed screw-and-disc type load brake stays clean and dry for positive load engagement.

**OPTIONS** - Shipyard hook available for 1 1/2 ton and 3 ton models.

Capacity		Model Number	Lift (ft.)*	Strands of Load Chain	Minimum Dist Between Hooks (in.)	Handle Length (in.)	Average Handle Effort (lbs.)	Net Weight (lbs.)
(lb)	(Ton)							
1500	3/4	LSB-1500B-5	5	1	11 5/8	9 1/4	46	12
1500	3/4	LSB-1500B-10	10	1	11 5/8	9 1/4	46	14
1500	3/4	LSB-1500B-15	15	1	11 5/8	9 1/4	46	16
1500	3/4	LSB-1500B-20	20	1	11 5/8	9 1/4	46	16
3000	1 1/2	LSB-3000B-5	5	1	13	14 9/16	59	21
3000	1 1/2	LSB-3000B-10	10	1	13	14 9/16	59	24
3000	1 1/2	LSB-3000B-15	15	1	13	14 9/16	59	27
3000	1 1/2	LSB-3000B-20	20	1	13	14 9/16	59	30
6000	3	LSB-6000B-5	5	1	16 5/16	14 9/16	75	35
6000	3	LSB-6000B-10	10	1	16 5/16	14 9/16	75	40
6000	3	LSB-6000B-15	15	1	16 5/16	14 9/16	75	45
6000	3	LSB-6000B-20	20	1	16 5/16	14 9/16	75	50
12000	6	LSB-12000B-5	5	2	22 3/4	14 9/16	76	67
12000	6	LSB-12000B-10	10	2	22 3/4	14 9/16	76	77
12000	6	LSB-12000B-15	15	2	22 3/4	14 9/16	76	88
12000	6	LSB-12000B-20	20	2	22 3/4	14 9/16	76	99

\* Standard lifts shown. Other lifts available.  
Please consult a Timberland Equipment Limited Representative.

**OUR PEOPLE CARE ...  
OUR EQUIPMENT IS THE PROOF**

## TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE

Timberland Equipment Limited  
www.timberland.on.ca

PO Box 490, 459 Industrial Avenue  
Woodstock, Ontario, Canada N4S 7Z2

Phone: (519) 537-6262  
Fax: (519) 539-5853

Web: www.timberland.on.ca  
Email: sales@tewinch.com

At Timberland, engineering is a process of continuous improvement therefore, specifications are subject to change without notice.