

SELF-LOADING REEL CARRIERS


Model	RCSL16 108 x 64	RCSL 20 108 x 64
Reel Capacity		
Max reel diameter	2742 mm (108")	2742 mm (108")
Min reel diameter (self-loading)	1524 mm (60")	1524 mm (60")
Max reel width	1624 mm (64")	1624 mm (64")
Max reel weight	7528 kg (16,000 lbs)	9072 kg (20,000 lbs)
Trailer Specifications		
Axle capacity	9072 kg (20,000 lbs)	10,886 kg (24,000 lbs)
Trailer brakes	Air-hydraulic	Air-hydraulic
Axle & suspension type	Tandem walking beam	
Jacks	Manual drop leg (1 front, 2 rear)	
Tow hitch	4 position with pin connections & safety chains	

GENERAL FEATURES

Hydraulic self-loading with hand pumps (or optional connections for external hydraulic supply)
 4 position reel rack with locking pins to mechanically lock and hold reel in loaded position
 Reel shaft with nylatron bushings

OPTIONS

Reel drive: pneumatic tire rim drive to wind up or payout cable under power, powered by external hydraulic source (tool circuit)
 Hydraulic power unit: to provide power for optional reel drive and / or hydraulic self-loading feature
 Reel shaft adapter bushings: to accommodate reels with larger diameter arbor holes
 Hydraulic jacks: front and rear, in lieu of mechanical drop leg jacks
 Wheel chocks
 Tool box

**OUR PEOPLE CARE ...
 OUR EQUIPMENT IS THE PROOF**

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE