

UNDERGROUND PULLER

SPECIFICATIONS

Maximum linepull:	18,140 daN (40,400 lbs) @ 4.25 m/min (14 fpm)
Maximum linespeed:	8.5 m/min (28 fpm)
Maximum rope diameter	28.5 mm (1.125")
Bullwheel nominal diameter	457 mm (18")
Power (diesel)	27.5 kW (37 hp)

DIMENSIONS

(approximate)

Weight (with rope)	4850 kg (10,700 lbs)
Length	4078 mm (160")
Width	2084 mm (82")
Height	1550 mm (61")

STANDARD EQUIPMENT

Fully hydraulic drive system
 Infinitely variable speed and linepull control
 Hydraulic oil cooler
 Water cooled diesel engine
 Linepull gauge
 Remote corded control
 Sheet metal enclosure with hinged panels
 Mechanical drop leg stabilizer
 Tandem axle trailer with lights, fenders, electric brakes
 Integral reel with hydraulic drive and capacity for 610m of 22mm wire rope
 Automatic diamond leadscrew levelwind
 Rear fairlead deflector sheave

OPTIONS

Wire rope: 22mm x 610m rotation resistant type
 Downhole jib
 Underground accessories

OUR PEOPLE CARE ...
OUR EQUIPMENT IS THE PROOF

TENSION STRINGING EQUIPMENT & ACCESSORIES CATALOGUE